

nappy changing units

- Large, concave changing beds fold away when not in use
- Strong safety straps with snap-lock fitting
- Gas strut mechanism breaks the closing motion to avoid trapped fingers
- Built-in liner dispenser holds hygienic paper liners
- Convenient positioning for wheelchair access
- Easy to recognise symbols for parents
- Braille instructions for the visually impaired
- Complete with full fixing kit for easy installation
- Suggested mounting height is 775mm to base of unit
- Maximum static load - 100Kgs

code description

74001	vertical Nappy changing unit
74002	horizontal Nappy changing unit
74005	stainless steel Nappy changing unit



technical specification

- The gas strut mechanism breaks the closing motion to avoid trapped fingers with the mounting supports being made of 10 gauge steel to provide exceptional weight distribution and stability
- The reinforced steel-on-steel hinge system prevents any wear on the plastic construction whilst the unique locking device holds the bed in the horizontal position.
- Steel rod and sleeve extend the whole width of the units and both Nappy Changing Units conform to ANS117.1 for handicapped accessibility
- Suggested mounting height meet with the requirements of M @ - section 3.1 of Building Regulations 1991 - access Facilities for disabled people
- All units meet exceed the international standards as follows:
 - BS 5799:1986 (where applicable)
 - BS 5665 part 3 Toxicity Test
 - AFNOR NF S 54-005 Changing Units
 - ASTM G-22 Bacterial
 - GS 2 PfG 913 Changing Units



Please note: Regulations may be subject to change without prior notice