


10 Amp 2 Way Switch

Dimensions

88x88x3mm



Variations

Switch	CBN	CPC	СРВ	CSC
Matching	CBNISW	CPCISW	CPBISW	CSCISW

2 Gang 10 Amp 2 Way Switch

Dimensions

88x88x3mm



Switch	CBN	CPC	СРВ	CSC
Matching	CBN2SW	CPC2SW	CPB2SW	CSC2SW





Switch	CBN	CPC	СРВ	CSC
Matching	CBN3SW	CPC3SW	CPB3SW	CSC3SW

CONTACT US FOR DETAILS ON AVAILABLE

GRID OR MODULE OPTIONS

TEL: 01772 672020

EMAIL: SALES@EUROLITE.CO.UK

WEB:WWW.EUROLITE.CO.UK

3 Gang

10 Amp 2 Way Switch

Dimensions

88x88x3mm



20 Amp DP Intermediate Switch

Dimensions

88x88x3mm



Variations

Switch	CBN	CPC	СРВ	CSC
Matching	CBNINT	CPCINT	CPBINT	CSCINT

20 Amp DP Switch

Dimensions

88x88x3mm



Switch	CBN	CPC	СРВ	CSC
Matching	CBN20ASW	CPC20ASW	CPB20ASW	CSC20ASW





Switch	CBN	CPC	СРВ	CSC
Matching	CBN20ASWN	CPC20ASWN	CPB20ASWN	CSC20ASWN

- CRABTREE INTERIOR
- NEXT DAY DELIVERY
- £100 CARRIAGE PAID
- COMPETITIVE PRICING

20 Amp DP Switch and Neon

Dimensions

88x88x3mm



13 Amp DP Switched Fuse Spur

Dimensions

88x88x3mm



Variations

Switch	CBN	CPC	СРВ	CSC
Matching Black	CBNSWFBNB	CPCSWFPCB	CPBSWFPBB	CSCSWFSCB
Matching White	N/A	CPCSWFPCW	CPBSWFPBW	CSCSWFSCW

13 Amp DP Switched Fuse and Neon

Dimensions

88x88x3mm



Switch	CBN	CPC	СРВ	CSC
Matching Black	CBNSWFNBNB	CPCSWFNPCB	CPBSWFNPBB	CSCSWFNSCB
Matching White	N/A	CPCSWFNPCW	CPBSWFNPBW	CSCSWFNSCW





Switch	CBN	CPC	СРВ	CSC
Matching	CBN45ASWNS	CPC45ASWNS	CPB45ASWNS	CSC45ASWNS



Switch	CBN	CPC	СРВ	CSC
Matching	CBNFSW	CPCFSW	CPBFSW	CSCFSW

45 Amp DP Cooker Switch Single Plate

Dimensions

88x88x3mm

Variations

Fan Isolator Switch Triple Pole

Dimensions


88x88x3mm



250W and 400W Dimmer Switch

Dimensions

88x88x3mm



Variations

Watt	CBN	CPC	СРВ	CSC
250VV	CBN1D250	CPC1D250	CPB1D250	CSC1D250
400VV	CBN1D400	CPCID400	CPBID400	CSCID400

2 Gang

250W and 400W Dimmer Switch

Dimensions

88x88x3mm




Watt	CBN	CPC	СРВ	CSC
250W	CBN2D250	CPC2D250	CPB2D250	CSC2D250
400W	CBN2D400	CPC2D400	CPB2D400	CSC2D400





Switch	CBN	CPC	СРВ	CSC
Matching Black Matching White	CBNISOB N/A	CPCISOB CPCISOW	CPB1SOB CPB1SOW	CSCISOB CSCISOW



Switch	CBN	CPC	СРВ	CSC
Matching Black Matching White	CBN2SOB N/A	CPC2SOB CPC2SOW	CPB2SOB CPB2SOW	CSC2SOB CSC2SOW

I3 Amp DP Switched Socket

Dimensions

88x88x3mm

Variations

2 Gang

13 Amp DP Switched Socket

Dimensions

148x88x3mm



5 Amp Unswitched Socket

Dimensions

88x88x3mm



Variations

Interior	CBN	CPC	СРВ	CSC
Black	CBN5AUSOB	CPC5AUSOB	CPB5AUSOB	CSC5AUSOB
White	N/A	CPC5AUSOW	CPB5AUSOW	CSC5AUSOW

45 Amp DP Switch and Socket

Dimensions

148x88x3mm



Switch	CBN	CPC	СРВ	CSC
Matching Black Matching White	CBN45ASWASB N/A	CPC45ASWASB CPC45ASWASW	CPB45ASWASB CPB45ASWASW	CSC45ASWASB CSC45ASWASW





Interior	CBN	CPC	СРВ	CSC
Black	CBN I SB	CPCISB	CPBISB	CSCISB
White	N/A	CPCISW	CPBISW	CSCISW



Interior	CBN	CPC	СРВ	CSC
Black	CBNIMB	CPCIMB	CPBIMB	CSCIMB
White	N/A	CPCIMW	CPBIMW	CSCIMW

Telephone Slave

Dimensions 88x88x3mm

Variations

Telephone Master

Dimensions 88x88x3mm



TV Outlet

Dimensions 88x88x3mm



Variations

Interior	CBN	CPC	СРВ	CSC
Black	CBNITVB	CPCITVB	CPBITVB	CSCITVB
White	N/A	CPCITVW	CPBITVW	CSCITVW

Sky + Socket

Dimensions 148x88x3mm



Interior	CBN	CPC	СРВ	CSC
Black	CBNSKY+B	CPCSKY+B	CPBSKY+B	CSCSKY+B
White	N/A	CPCSKY+W	CPBSKY+W	CSCSKY+W






Shaver Socket

Dimensions 88x148x3mm



Blank Plate

Dimensions 88x88x3mm



Variations

CBN	CPC	СРВ	CSC
CBNIB	CPCIB	СРВІВ	CSCIB

2 Gang

Blank Plate

Dimensions

148x88x3mm



CBN	CPC	СРВ	CSC
CBN2B	CPC2B	CPB2B	CSC2B



Eurolite utilise Crabtree capital power and control interiors which are fully design co-ordinated to offer consistent styling and inherent safety features across a broad range of applications.

Features include:


- Large concave rockers for ease of operation especially for the elderly and infirm.
- Labyrinth switch design to minimise visible arc flash and prevents front access to live parts.
- Large tunnel terminals with Live and Neutral angled for ease of wiring and to assist installation.
- Socket outlets with twin earth terminals as standard for high integrity earthing.
- Padlockable Fused Connection Unit carrier for extra on-site maintenance safety.
- Optional neon indicator for visual "ON".
- Positive drive action prevents balancing between ON and OFF position.
- Double pole product marking on moulded rocker to easily identify once product has been installed.
- Substantial silver alloy contacts for longer life and low contact resistance.
- 3mm contact gap ensures safe means of isolation.
- Individually boxed to protect product before installation.
- Metal rockers to harmonise with the decorative plate finish.
- Modular grid products enables units to be quickly and easily assembled to customers' individual specifications
 allowing several circuits to be controlled from a single position.

RECOMMENDED QUANTITY OF SOCKET OUTLETS FOR DOMESTIC INSTALLATIONS

An installation may have too few socket outlets or the existing socket outlets may be incorrectly sited. Both conditions are symptomatic of an inadequate installation which could lead to potentially dangerous improvisation. The following is a summary of the recommendations of the Electrical Installation Industry Liaison Committee and all socket outlets should be of the twin switched type.

NUMBER OF SOCKETS ROOM	6	6	4
	KITCHEN	LOUNGE	DINING ROOM
4	4	4	I
DOUBLE BEDROOM	SITTING ROOM	SINGLE BEDROOM	LANDING/STAIRS
2 HALL	2 GARAGE	2 STORE/WORKROOM	I CENTRAL HEATING BOILER POINT

GUIDE TO THE TERMINAL CAPACITIES OF THE PRINCIPAL WIRING ACCESSORIES - PRODUCT/CONDUCTOR SIZE



13A SOCKET OUTLETS
13A FUSED CONNECTION UNITS
10AX PLATE SWITCHES
20A DP SWITCHES

3 x 2.5mm², 2 x 4mm², 2 x 6mm² 3 x 2.5mm², 2 x 4mm², 2 x 6mm² 4 x Imm², 3 x I.5mm², I x 2.5mm² 3 x 2.5mm², 2 x 4mm², I x 6mm², I x 10mm²